



Rating:
 7A 125V AC UL cUL
 2.5A 250V AC VDE 3C KC
 Insert And Extract Force: 20N~50N
 Terminal Strength: ≥60N
 Operating Life: ≥6000 cycles
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
 Terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current: 1mA
 Insulation Resistance: >100MΩ 500V DC
 Body Material: NYLON 66 94V-2-0

序号	名称	材料	处理	数量	备注
1	DB-8-1塑料件	环阻PA66	黑色	1	
2	DB-8-P2L端子	黄铜	镀锡	1	Plating Thickness >80u''
3	DB-8-P2R端子	黄铜	镀锡	1	Plating Thickness >80u''
4	DB-8-1DX短插销	黄铜	镀镍	2	Plating Thickness 40u''-80u''

55*32*25cm箱, 200只*36袋装=2.4k件, 净重:9.7 毛重:11.7=KG,

普通公差:	
COMMON TOLERANCE :	
UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV.	DATE	REVISION DESCRIPTION	ISSUE	单位	mm	投影	品名	Ac Inlet C8型	比例	Free
				UNIT		PROJECTED	PRODUCT NAME		SCALE	
				绘图	金泽杰	核对	型号			
				DRAWN BY		CHECKED BY	MODEL NO.			
				日期	2022/2/16	核准	料号			
				DATE		APPROVAL BY	PART NO.			DB-8-1P2-ZP