



Rating:

7A 125V AC UL cUL
 2.5A 250V AC VDE 3C KC
 Insert And Extract Force: 1.36kgf ~ 6.8kgf
 Operating Life: >5000 cycles
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
 Terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current: 1mA
 Insulation Resistance: >100MΩ 500V DC
 Body Materil: NYLON66 94V-2~0

序号	名称	材料	处理	数量	备注
1	DB-8-1塑料件	环阻PA66	黑色	1	
2	DB-8-S1端子	黄铜	镀锡	2	
3	DB-8-1DX短插销	黄铜	镀镍	2	

55*32*25cm箱, 200只*18袋装=3.6k件, 净重:15.9 毛重:18.4=KG,

普通公差:
COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONI CS CO., LTD.

REV.	DATE	REVISION DESCRIPTION	ISSUE	单位 UNIT	mm	投影 PROJECTED	品名 PRODUCT NAME	AC Inlet C8型	比例 SCALE	Free
				绘图 DRAWN BY	金泽杰	核对 CHECKED BY	张春花	型号 MODEL NO.		
				日期 DATE	2022/2/12	核准 APPROVAL BY	同培雷	料号 PART NO.	DB-8-1S1-ZP	