



PANEL CUT-OUT

Rating:

7A 125V AC UL cUL
2.5A 250V AC VDE 3C KC

Insert And Extract Force: 20N~50N

Operating Life: ≥6000 cycles

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min

Terminals to Base: 3750V AC (50-60Hz) 1min

Leakage Current: 1mA

Insulation Resistance: >100MΩ 500V DC

Body Material: NYLON 66 94V-2-0

序号	名称	材料	处理	数量	备注
1	DB-8-4塑料件	环阻PA66	黑色	1	
2	DB-8-P6端子	黄铜	镀锡	2	Plating Thickness >80u''
3	DB-8-1DX圆针	黄铜	镀镍	2	Plating Thickness 40u''-80u''

55*32*25cm箱, 100只*30吸盒装=3k件, 净重:12.9 毛重:14.9=KG,

普通公差:
COMMON TOLERANCE :

UP TO 5	±0.20
ABOVE 5 TO 30	±0.30
ABOVE 30	±0.50
ANGULAR	±5°



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV.	DATE	REVISION DESCRIPTION	ISSUE	单位	mm	投影	品名	Ac Inlet C8型	比例	Free
				UNIT		PROJECTED	PRODUCT NAME		SCALE	
				绘图	金泽杰	核对	型号		/DB-8	
				DRAWN BY		CHECKED BY	料号			
				日期	2021/12/7	核准	PART NO.			
				DATE		APPROVAL BY				DB-8-4P6-ZP