



Rating:
 7A 125V AC UL cUL
 2.5A 250V AC VDE 3C KC
 Insert And Extract Force: 20N~50N
 Terminal Strength: >60N
 Operating Life: >6000 cycles
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
 Terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current: 1mA
 Insulation Resistance: >100MΩ 500V DC
 Body Material: NYLON66 94V-2-0

序号	名称	材料	处理	数量	备注
1	DB-8-4P8塑料件	环阻PA66	黑色	1	
2	DB-8-P8端子	黄铜	镀锡	2	
3	DB-8-1DX圆针	黄铜	镀镍	2	

55*32*25cm箱, 140只*28吸盒装=4k件, 净重: 16.4毛重: 18.4=KG,

		普通公差: COMMON TOLERANCE :		东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.							
		UP TO 5	±0.20							单位 UNIT	mm
		ABOVE 5 TO 30	±0.30	绘图 DRAWN BY	金泽杰	核对 CHECKED BY	张彦龙	型号 MODEL NO.	/DB-8		
REV.	DATE	REVISION DESCRIPTION	ISSUE	日期 DATE	2022/5/17	核准 APPROVAL BY	同培南	料号 PART NO.	DB-8-4P8-ZP		
		ABOVE 30	±0.50								
		ANGULAR	±5°								