



Rating:

7A 125V AC UL cUL

2.5A 250V AC VDE 3C KC

Insert And Extract Force: 20N~50N

Operating Life: >6000 cycles

Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min

Terminals to Base: 3750V AC (50-60Hz) 1min

Leakage Current: 1mA

Insulation Resistance: >100MΩ 500V DC

Body Material: PC 94V-2~0

55*43*23.5cm箱, 40只*56吸盒装=2.24k件, 净重:11 毛重:13=KG,

序号	名称	材料	处理	数量	备注
1	DB-8-6塑料件	PC	黑色	1	
2	DB-8-S1端子	黄铜	镀锡	2	Plating Thickness >80u''
3	DB-8-3C圆针	黄铜	镀镍	2	Plating Thickness 40u''-80u''

普通公差:

COMMON TOLERANCE :

UP TO 5 ±0.20

ABOVE 5 TO 30 ±0.30

ABOVE 30 ±0.50

ANGULAR ±5°

单位

mm

绘图

金泽杰

日期

2021/11/2



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

投影



核对

张军龙

核准

周培雷

品名

Ac Inlet C8型

型号

/DB-8

料号

DB-8-6S1-ZP

REV.	DATE	REVISION DESCRIPTION	ISSUE	普通公差:	COMMON TOLERANCE :	单位	mm	投影	品名	Ac Inlet C8型	比例	Free
				UP TO 5	±0.20	绘图	金泽杰	核对	张军龙	型号	/DB-8	
				ABOVE 5 TO 30	±0.30	日期	2021/11/2	核准	周培雷	料号	DB-8-6S1-ZP	
				ABOVE 30	±0.50							
				ANGULAR	±5°							