



| X | Y |
|-----|------|
| 1.0 | 24.5 |
| 1.2 | 24.5 |

Rating :
 7A 125V AC UL cUL
 2.5A 250V AC VDE 3C KC
 Insert And Extract Force: 20N~50N
 Operating Life: ≥6000 cycles
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min
 terminals to Base: 3750V AC (50-60Hz) 1min
 Leakage Current : 1mA
 Insulation Resistance: ≥100MΩ 500V DC
 Body Materil: PC 94V-2-0

| 序号 | 名称 | 材料 | 处理 | 数量 | 备注 |
|----|---------------|------|----|----|--------------------------------|
| 1 | DB-8-6(L) 塑料件 | 环阻PC | 黑色 | 1 | |
| 2 | DB-8-S1端子 | 黄铜 | 镀锡 | 1 | Plating Thickness >80u'' |
| 3 | DB-8-3C插销 | 黄铜 | 镀镍 | 2 | Plating Thickness 40u'' -80u'' |

55*32*25cm箱, 200只*18袋装=3.6k件, 净重:17.3 毛重:19.3=KG,

| | | | | | | | | | | | | | |
|------|------|----------------------|-------|--------------------|-------|---|------------|-----|-----|----|--------------|--------|----------------|
| A4 | | | | 普通公差 | | 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD. | | | | | | | |
| A3 | | | | COMMON TOLERANCE : | | | | | | | | | |
| A2 | | | | UP TO 10 | ±0.10 | 单位 | mm | 投影 | | 品名 | Ac Inlet C8型 | 比例 | Free |
| A1 | | | | ABOVE 10 TO 30 | ±0.30 | 绘图 | 金泽杰 | 核对应 | 张华龙 | 型号 | | :/DB-8 | |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ABOVE 30 | ±0.50 | 日期 | 2021/11/26 | 核准 | 同培雷 | 料号 | | | |
| | | | | ANGULAR | ±5° | 日期 | | 核准 | | 料号 | | | DB-8-6S1(L)-ZP |