



Rating :  
 15A 250V AC UL cUL  
 10A 250V AC 3C VDE  
 Insert And Extract Force: 1.36kgf~6.8kgf  
 Terminal Strength: ≥60N  
 Operating Life: ≥6000 cycles  
 Withstand Voltage: Between all terminals: 2500VAC (50-60Hz) 1min  
 Terminals to Base: 3750V AC (50-60Hz) 1min  
 Leakage Current: 1mA  
 Insulation Resistance: ≥100MΩ 500V DC  
 Body Materil: PA66 94V-2~0

序号	名称	材料	处理	数量	备注
1	DB-14-1J塑料件	还阻PA66	黑色	1	
2	DB-14-F6L(1.0)长插销	黄铜	镀锡	1	
3	DB-14-F6S(1.0)长插销	黄铜	镀锡	2	
4	DC-12-1A盖板	还阻PA66	黑色	1	
5	DC-12-1A扭簧	黄铜	镀锡	1	

				普通公差: COMMON TOLERANCE :		 <b>东莞市溪榜电子有限公司</b> DONG GUAN XI BANG ELECTRONI CS CO., LTD.											
		UP TO 5	±0.20	单位	mm							投影		品名	Ac Inlet C14型	比例	Free
		ABOVE 5 TO 30	±0.30	绘图	金泽林							核对	张军龙	型号	DB-14		
		ABOVE 30	±0.50	日期	2023. 2. 7							批准	王天建	料号	DB-14-1JF6(1.0) (G)		
REV.	DATE	REVISION DESCRIPTION	ISSUE	ANGULAR	±5°												