



Specifications

Current Rating:1.1Amp
 Insulation Resistance:10000MΩMin.
 Dielectric Withstanding Voltage:500VAC
 Contact Resistance:10mΩMax.
 Operating Temperature:-55°C to +125°C
 Materials

Contact Material:Phosphor Bronze
 Insulator Material:High Temperature Thermoplastic, UL 94V-0 LCP or the equivalent material
 All materials must meet **XI BANG** hazardous substances control standards.

★:Critical Characteristics.
 indicates product characteristics, functionalities,and manufacturing processes regarding to customer's specifications

☆:Safety Features
 indicates product characteristics, functionalities, and manufacturing processes complying to legal regulations stated by local government

Ordering Information

XB-IDC-217 - XX XX A 002 C 1 S X

No. of Pins per Row
 06,10,13,16,25,
 34,40

Standard Plating
 77=15u" gold plating on
 contact area, matte tin
 plating on solder area

Color
 1=Black

Standard Packing
 B=Tray

No. of Pin/Row	Dimension Information			
	M	L1	L	D
2X6	6.35	8.37	9.37	14.71
2X10	11.43	13.45	14.45	19.79
2X13	15.24	17.26	18.26	23.60
2X16	19.05	21.07	22.07	27.41
2X25	30.48	32.50	33.50	38.84
2X34	41.91	43.93	44.93	50.27
2X40	49.53	51.55	52.55	57.89

XB 东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD

3RD.ANG
 PROJ.

GENERAL TOLERANCE	
X. ± 5.0'	X. ± 0.30
.X' ± 3.0'	.X ± 0.25
.XX' ± 2.0'	.XX ± 0.15
.XXX' ± 1.0'	.XXX ± 0.10

DESIGNED:

DATE:

DWG. NO.

XB-IDC-217

TITLE.

IDC Female Connector
 Type B with Locking Latches

CHECKED:

DATE:

PART NO.

APPROVED:

DATE:

REV. B UNIT. mm SCALE. 5:3 PAGE. 1/1