



Technical Specs:
 Insulator:Black glass filled polyester PPS-GF30-FR
 Flammability:UL 94V-0
 Contact:Brass CuZn36Pb3(C36000)
 Rated current:1A
 Contact resistance:max 10 mΩ
 Dielectric strength:min 1,000 V RMS
 All materials must meet XI BANG
 hazardous substances control standards.

No. of PIN/ROW	M	L
01	0	1.68
02	1.27	2.95
03	2.54	4.22
04	3.81	5.49
05	5.08	6.76
06	6.35	8.03
07	7.62	9.30
08	8.89	10.57
09	10.16	11.84
10	11.43	13.11
11	12.70	14.38
12	13.97	15.65
13	15.24	16.92
14	16.51	18.19
15	17.78	19.46
16	19.05	20.73
17	20.32	22.00
18	21.59	23.27
19	22.86	24.54
20	24.13	25.81
21	25.40	27.08
22	26.67	28.35
23	27.94	29.62
24	29.21	30.89
25	30.48	32.16
26	31.75	33.43
27	33.02	34.70
28	34.29	35.97
29	35.56	37.24
30	36.83	38.51
31	38.10	39.78
32	39.37	41.05
33	40.64	42.32
34	41.91	43.59
35	43.18	44.86
36	44.45	46.13
37	45.72	47.40
38	46.99	48.67
39	48.26	49.94
40	49.53	51.21

Ordering Information

XB-PM-Y-127X-201 - XX XX A 002 S X B X

No. of Pins per Row 01~40
 Standard Plating 01=TIN
 02=Gold Flash
 B1=Gold 3U"

Color 1=Black
 Standard Packing C=Tube
 N=PE Bag

东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO.,LTD

3RD.ANG PROJ.

 PAGE. 1/1

GENERAL TOLERANCE	
X.*±3.0'	X.±/
.X*±3.0'	.X±0.30
.XX*±3.0'	.XX±0.25
.XXX*±3.0'	.XXX±0.20

DESIGNED:
 CHECKED:
 APPROVED:

DATE:
 DATE:
 DATE:

DWG. NO.
 XB-PM-Y-127X-201-A002
 PART NO.

TITLE.
 1.27mm PIN CONNECTOR
 H=2.2mm DIP

REV. A UNIT. mm SCALE. 1:1